




## ROUND PIPE




SIDE ELEVATION



FRONT ELEVATION




SECTION A-A




FRONT ELEVATION MULTIPLE PIPES


## ARCH PIPE




SIDE ELEVATION



FRONT ELEVATION



SECTION B-B



FRONT ELEVATION MULTIPLE PIPES

NOTE:  
ALL CONCRETE IS CLASS  
GENERAL OR EQUAL.

UNITS SHOWN IN BRACKETS [ ] ARE  
METRIC AND ARE IN MILLIMETERS (mm)  
UNLESS OTHER UNITS ARE SHOWN.






### DETAILED DRAWING

REFERENCE	DWG. NO.
STANDARD SPEC.	613-06
SECTION 613, 603, 552	

CONCRETE EDGE PROTECTION  
FOR METAL CULVERTS

**ROUND PIPE**  
(FETS SHOWN)

**ARCH PIPE**  
(FETS SHOWN)





CONCRETE CUTOFF WALL INLET AND OUTLET END SEE DTL. DWG. NO. 552-00 (WHEN SPECIFIED IN PLANS)

NOTES:

- ① ALL CONCRETE IS CLASS GENERAL CONCRETE OR EQUAL.
- ② SEE DTL. DWG. NO. 603-08 AND 603-10 FOR RCP AND RCPA CULVERTS WITH FETS. FOR RCP AND RCPA CULVERTS WITH SQUARE ENDS, THE "X" DIMENSION IS D/4 OR R/3.

UNITS SHOWN IN BRACKETS [ ] ARE METRIC AND ARE IN MILLIMETERS (mm) UNLESS OTHER UNITS ARE SHOWN.

DETAILED DRAWING	
REFERENCE	DWG. NO.
STANDARD SPEC.	613-08
SECTION 613,603,552	
CONCRETE EDGE PROTECTION FOR CONCRETE CULVERTS	
<b>MDT</b> MONTANA DEPARTMENT OF TRANSPORTATION	



**CAST-IN-PLACE CONCRETE:**

LOCATE JOINTS AS INDICATED ON THE PLANS. IF CONSTRUCTION IS STOPPED FOR OVER TWO HOURS, CREATE A CONSTRUCTION JOINT. USE CLASS GENERAL CONCRETE FOR ALL CAST-IN-PLACE CONCRETE.

USE A 1/2" [13] EXPANSION JOINT FILLER PER SECTION 707 WHENEVER THE CAST-IN-PLACE CONCRETE ABUTS AGAINST ANY PART OF THE BRIDGE STRUCTURE.






CLEAR THE EMBANKMENT SLOPE OF ALL BRUSH, DEBRIS AND RUBBLE. A CUSHION IS NOT REQUIRED FOR GRAVEL EMBANKMENT SLOPES. FINISH ALL SLOPES TO THE SLOPE INDICATED IN THE BRIDGE PLANS. COMPACT ALL LOOSE MATERIAL. LEAVE THE ADJACENT SLOPE AREA IN A SMOOTH, UNIFORM CONDITION.

**REINFORCING STEEL:**

(MAY USE EITHER ALTERNATE LISTED BELOW)

- #3 [#10] BARS AT 10' [250] O.C. (HORIZONTAL AND VERTICAL SPACING) MIN. COVER OF 2" [50]
- 6' x 6' x W2.9 [152.4 x 152.4 x MW18.7] WIRE MESH

12" [300] OVERLAP REQUIRED AT CONSTRUCTION JOINTS FOR REINFORCING STEEL AND WIRE MESH.



**VERTICAL AND HORIZONTAL CONSTRUCTION JOINT**

USE AS NEEDED IN PLACING SLAB. WHEN REQUIRED, USE IN LIEU OF A DIMENSION JOINT AT THE SAME SPACING AS A DIMENSION JOINT.

JOINTS MAY BE SAWS, MADE WITH GROOVING TOOLS OR REMOVABLE INSERTS OF AN APPROVED TYPE.

IF JOINTS ARE TO BE SAWS, SAW JOINTS JUST AFTER CONCRETE HAS SET BUT BEFORE UNCONTROLLED CRACKING OCCURS.


**VERTICAL AND HORIZONTAL DIMENSION JOINT**

6' [1800] VERTICAL SPACING OR AS NOTED.  
8' [2400] HORIZONTAL SPACING OR AS NOTED.  
JOINTS MAY BE SAWS, MADE WITH GROOVING TOOLS OR REMOVABLE INSERTS OF AN APPROVED TYPE.


DETAILED DRAWING	
REFERENCE	DWG. NO.
STANDARD SPEC.	613-10
SECTION 613.707	

CONCRETE SLOPE PROTECTION

UNITS SHOWN IN BRACKETS [ ] ARE METRIC AND ARE IN MILLIMETERS (mm) UNLESS OTHER UNITS ARE SHOWN.




PLAN



ELEVATION

INLET HEADWALL

CHAMFER ALL EXPOSED CORNERS 1" (25). REINFORCING STEEL TO BE NOT LESS THAN 1 1/2" (40) TO NEAREST FACE OF CONCRETE.



SECTION A-A

INLET AND OUTLET HEADWALLS FOR CMP												
CULVERT		CL. GENERAL CONC. OR EQUAL (C.Y.)		* REBAR #4 (L.B.)		DIMENSION TABLE						
DIA. D	AREA (SQ. FT.)	INLET	OUTLET	INLET	OUTLET	A	B	H	L	L'	F	L'
18"	1.77	0.73	0.59	70	60	1'-3"	1'-3"	2'-6"	2'-6"	1'-9"	6"	2'-2"
24"	3.14	0.91	0.76	83	73	1'-6"	1'-6"	3'-0"	3'-0"	2'-1"	6"	2'-6"
30"	4.91	1.06	0.95	109	93	1'-9"	1'-9"	3'-6"	3'-6"	2'-6"	6"	2'-10"
36"	7.07	1.68	1.11	127	108	2'-0"	2'-0"	4'-0"	4'-0"	2'-10"	6"	3'-2"
42"	9.62	2.10	1.40	153	125	2'-3"	2'-3"	4'-6"	4'-6"	3'-2"	6"	3'-6"
48"	12.57	2.32	1.66	178	149	2'-6"	2'-6"	5'-0"	5'-0"	3'-6"	6"	3'-10"

\* FOR INFORMATION PURPOSES ONLY INCLUDE IN THE COST OF CLASS DD CONCRETE

METRIC INLET AND OUTLET HEADWALLS FOR CMP												
CULVERT		CL. GENERAL CONC. OR EQUAL (m <sup>3</sup> )		* REBAR #13 (kg)		METRIC DIMENSION TABLE (mm)						
DIA. D (mm)	AREA (m <sup>2</sup> )	INLET	OUTLET	INLET	OUTLET	A	B	H	L	L'	F	L'
450	0.159	0.6	0.5	32	27	400	400	800	750	550	150	650
600	0.283	0.8	0.6	38	33	450	450	900	900	650	150	750
750	0.442	1.1	0.8	50	42	550	550	1100	1050	750	150	850
900	0.636	1.3	0.9	57	49	600	600	1200	1200	850	150	950
1050	0.866	1.6	1.1	69	57	700	700	1400	1350	950	150	1050
1200	1.131	1.8	1.3	81	68	750	750	1500	1500	1050	150	1150


\* FOR INFORMATION PURPOSES ONLY INCLUDE IN THE COST OF CLASS DD CONCRETE

INLET AND OUTLET HEADWALLS FOR RCP												
CULVERT		CL. GENERAL CONC. OR EQUAL (C.Y.)		* REBAR #4 (L.B.)		DIMENSION TABLE						
DIA. D	AREA (SQ. FT.)	INLET	OUTLET	INLET	OUTLET	A	B	H	L	L'	F	L'
18"	1.77	0.80	0.60	71	61	1'-3"	1'-3"	2'-6"	2'-6"	1'-9"	6 1/2"	2'-2"
24"	3.14	1.00	0.86	85	75	1'-6"	1'-6"	3'-0"	3'-0"	2'-1"	7"	2'-6"
30"	4.91	1.42	1.14	112	95	1'-9"	1'-9"	3'-6"	3'-6"	2'-6"	7 1/2"	2'-10"
36"	7.07	1.84	1.43	129	111	2'-0"	2'-0"	4'-0"	4'-0"	2'-10"	8"	3'-2"
42"	9.62	2.12	1.73	156	128	2'-3"	2'-3"	4'-6"	4'-6"	3'-2"	8 1/2"	3'-6"
48"	12.57	2.34	2.07	182	152	2'-6"	2'-6"	5'-0"	5'-0"	3'-6"	9"	3'-10"


\* FOR INFORMATION PURPOSES ONLY INCLUDE IN THE COST OF CLASS DD CONCRETE

METRIC INLET AND OUTLET HEADWALLS FOR RCP												
CULVERT		CL. GENERAL CONC. OR EQUAL (m <sup>3</sup> )		* REBAR #13 (kg)		METRIC DIMENSION TABLE (mm)						
DIA. D (mm)	AREA (m <sup>2</sup> )	INLET	OUTLET	INLET	OUTLET	A	B	H	L	L'	F	L'
450	0.164	0.7	0.5	32	28	400	400	800	750	550	200	650
600	0.292	0.8	0.6	38	34	450	450	900	900	650	200	750
750	0.456	1.1	0.8	51	43	550	550	1100	1050	750	200	850
900	0.657	1.4	1.0	59	50	600	600	1200	1200	850	250	950
1050	0.894	1.7	1.2	71	58	700	700	1400	1350	950	250	1050
1200	1.167	2.0	1.4	82	69	750	750	1500	1500	1050	250	1150


\* FOR INFORMATION PURPOSES ONLY INCLUDE IN THE COST OF CLASS DD CONCRETE



PLAN



SECTION B-B





ELEVATION

OUTLET HEADWALL

UNITS SHOWN IN BRACKETS ( ) ARE METRIC AND ARE IN MILLIMETERS (mm) UNLESS OTHER UNITS ARE SHOWN.

DETAILED DRAWING  
 REFERENCE DWG. NO.  
 STANDARD SPEC. 613-12  
 SECTION 613  
 INLET AND OUTLET HEADWALLS FOR RCP AND CMP PIPES

MDT MONTANA DEPARTMENT OF TRANSPORTATION




NOTES:

- ① CULVERT RIPRAP IS ONLY USED IN SPECIAL CIRCUMSTANCES.
- ② KEY ENDS OF RIPRAP WALLS INTO THE EMBANKMENT SLOPES A MINIMUM OF 2 FEET [600 mm] FROM OUTER FACE OF THE RIPRAP FOR THE FULL HEIGHT OF THE RIPRAP WALL.

UNITS SHOWN IN BRACKETS [ ] ARE METRIC AND ARE IN MILLIMETERS (mm) UNLESS OTHER UNITS ARE SHOWN.


DETAILED DRAWING	
REFERENCE STANDARD SPEC. SECTION 613	DWG. NO. 613-14

CULVERT RIPRAP




**EMBANKMENT PROTECTION**

MINIMUM T FOR:  
 CLASS I RIPRAP = 1.5' [450]  
 CLASS II RIPRAP = 2.5' [750]  
 CLASS III RIPRAP = 3.0' [900]




**SECTION A-A**



**GEOTEXTILE PLACEMENT DETAIL**

METHOD FOR PLACING PERMANENT EROSION CONTROL GEOTEXTILE FOR PROTECTION OF STREAM BANKS



**GEOTEXTILE PLACEMENT DETAIL**

METHOD FOR PLACING PERMANENT EROSION CONTROL GEOTEXTILE FOR PROTECTION OF CUT AND FILL SLOPES

NOTES:

- ① INSTALL PERMANENT EROSION CONTROL GEOTEXTILE PER SECTION 622.


UNITS SHOWN IN BRACKETS [ ] ARE METRIC AND ARE IN MILLIMETERS (mm) UNLESS OTHER UNITS ARE SHOWN.

DETAILED DRAWING	
REFERENCE STANDARD SPEC. SECTION 613, 622	DWG. NO. 613-16


RIPRAP SLOPE PROTECTION



**RIPRAP & GROUTED RIPRAP DRAINAGE CHUTE**




**TURF REINFORCEMENT MAT DRAINAGE CHUTE**



TYPE	DIMENSIONS			RIPRAP CLASS	QUANTITIES			
	A	B	C		RIPRAP	GROUTED RIPRAP	TURF REINFORCEMENT MAT	ADD. RIPRAP FOR TRM CHUTES
1	2'-0"	4'-0"	1'-0"	I	5.23 C.Y. + (N x 0.506) C.Y./L.F.	* 7.84 S.Y. + (N x 0.759) S.Y./L.F.	6.96 S.Y. + (N x 0.537) S.Y./L.F.	* 1.5 C.Y.
2	2'-0"	4'-0"	1'-6"	I	5.42 C.Y. + (N x 0.563) C.Y./L.F.	* 8.13 S.Y. + (N x 0.845) S.Y./L.F.	7.25 S.Y. + (N x 0.623) S.Y./L.F.	* 2.2 C.Y.
3	4'-0"	8'-0"	1'-6"	II	15.86 C.Y. + (N x 0.815) C.Y./L.F.	* 23.80 S.Y. + (N x 1.222) S.Y./L.F.	22.02 S.Y. + (N x 1.000) S.Y./L.F.	* 9.8 C.Y.
4	4'-0"	8'-0"	2'-0"	II	16.18 C.Y. + (N x 0.863) C.Y./L.F.	* 24.27 S.Y. + (N x 1.293) S.Y./L.F.	22.49 S.Y. + (N x 1.073) S.Y./L.F.	* 13.0 C.Y.

TYPE	METRIC DIMENSIONS			RIPRAP CLASS	METRIC QUANTITIES			
	A	B	C		RIPRAP	GROUTED RIPRAP	TURF REINFORCEMENT MAT	ADD. RIPRAP FOR TRM CHUTES
1	600	1200	300	I	3.81 m <sup>2</sup> + (N x 1.229) m <sup>2</sup> /m	* 6.35 m <sup>2</sup> + (N x 2.049) m <sup>2</sup> /m	5.63 m <sup>2</sup> + (N x 1.449) m <sup>2</sup> /m	* 1.2 m <sup>3</sup>
2	600	1200	450	I	3.95 m <sup>2</sup> + (N x 1.369) m <sup>2</sup> /m	* 6.59 m <sup>2</sup> + (N x 2.282) m <sup>2</sup> /m	5.87 m <sup>2</sup> + (N x 1.682) m <sup>2</sup> /m	* 1.7 m <sup>3</sup>
3	1200	2400	450	II	11.57 m <sup>2</sup> + (N x 1.980) m <sup>2</sup> /m	* 19.28 m <sup>2</sup> + (N x 3.300) m <sup>2</sup> /m	17.84 m <sup>2</sup> + (N x 2.700) m <sup>2</sup> /m	* 7.5 m <sup>3</sup>
4	1200	2400	600	II	11.79 m <sup>2</sup> + (N x 2.098) m <sup>2</sup> /m	* 19.66 m <sup>2</sup> + (N x 3.497) m <sup>2</sup> /m	18.22 m <sup>2</sup> + (N x 2.897) m <sup>2</sup> /m	* 10.0 m <sup>3</sup>



UNITS SHOWN IN BRACKETS ( ) ARE METRIC AND ARE IN MILLIMETERS (mm) UNLESS OTHER UNITS ARE SHOWN.

DETAILED DRAWING  
REFERENCE DWG. NO.  
STANDARD SPEC. 613-18  
SECTION 613.701, 713.716

DRAINAGE CHUTES

\* USE CLASS-I RIPRAP FOR ALL GROUTED RIPRAP TYPES & TRM CHUTES