

# CONCRETE-FILLED STEEL TUBE TO CONCRETE PILE CAP CONNECTIONS – FURTHER EVALUATION/IMPROVEMENT OF ANALYSIS/DESIGN METHODOLOGIES

Cash Cota, MS<sup>1</sup>; Michael Berry, PhD<sup>1</sup>; Kirsten Matteson, PhD<sup>1</sup>  
<sup>1</sup>Montana State University

## INTRODUCTION

The Montana Department of Transportation (MDT) has found concrete-filled steel tube (CFST) piles connected at the top by a concrete pile cap to be a very cost-effective support system for short and medium span bridges. A typical pile cap using this system is shown in Figure 1. This type of system offers low initial cost, short construction time, low maintenance requirements, and a long service life. While the gravity load performance of these systems is well understood, their strength and ductility under extreme lateral loads (e.g., seismic events) is more difficult to reliably predict using conventional design procedures. This project aims to further develop newly established design and analysis methodologies through experimental testing to ultimately ensure bridge performance is fully consistent with design intent.



Figure 1. Typical MDT concrete-filled steel pile and concrete pile cap bridge substructure support system (Pryor Creek Bridge near Huntley, MT – courtesy of MDT (2012))

## EXPERIMENTAL DESIGN

An experimental program was developed to address the shortcomings identified in this analysis. Specifically, the proposed experimental design varied load setup (testing specimens vertically rather than on their sides, Figure 2), specimen scale, and reinforcement details relative to the original experiments. The results from this test series will be used to further establish the efficacy of the MDT design/analysis methodologies. A total of four specimens were designed and tested in this research.




Figure 2. Testing Set Up

## SPECIMEN OVERVIEW

- Specimen 1 – VT1/2-4 (“Verification Test, ½ Scale, 4 ksi Target Concrete Strength”) was tested to provide continuity from the previous testing at MSU and determine whether the testing orientation had any large effects on the results.
- Specimen 2 – VT2/3-4 was tested to isolate the effects of specimen size by keeping the concrete strength constant and changing the scale of the model.
- Specimen 3 – VT2/3-6 was tested to isolate the effects of concrete strength by keeping the size of the model constant and changing the strength of the concrete.
- Specimen 4 – VT2/3-4U (“U” indicates addition of U-bars) was tested to observe the effects of adding U-bars around the embedded tip of the pile (Figure 3).








Figure 3. Addition of U-bars to VT2/3-4U

## TEST RESULTS


**VT1/2-4** – Failed in the pile cap due to a combination of failure mechanisms.



**VT2/3-4** – Failed in the pile cap due to a combination of failure mechanisms.



**VT2/3-6** – Failed in the pile cap due to a combination of failure mechanisms.



**VT2/3-4U** – Failure was forced into the CFST, a desired failure mechanism





Figure 4. Moment-Drift Reponses Curves (Left) and photos of damage (Right) from each specimen

Table 1. Summary of Results

Specimen Name	Concrete Strength (psi)	Specimen Scale	Reinforcing Scheme	First Crack Moment (k-ft)	45° Crack Moment (k-ft)	Gap Formation Moment (k-ft)	Failure Mechanism	Ultimate Moment (k-ft)	Predicted Moment (k-ft)	Measured/Predicted Ratio
VT1/2-4	4000	1/2 Scale	Normal	47.3	63	63	Cap Failure-Crushing Cracking	101.5	111.9	0.91
VT2/3-4	4000	2/3 Scale	Normal	69	115	92	Cap Failure-Crushing Cracking	208.3	232.5	0.90
VT2/3-6	5500	2/3 Scale	Normal	92	138	115	Cap Failure-Crushing Cracking	276.7	304	0.91
VT2/3-4U	4800	2/3 Scale	U-Bars Added	92	184	230	Plastic Hinge in CFT	332.3	301.6	1.10
Average =										0.95
Coeff. Of Variation =										0.104

## CONCLUSIONS AND RECOMMENDATIONS

Based on the results of this research, the following conclusions were made:

1. Specimens without U-bars demonstrated the same overall moment-drift response, progression of damage, and failure mechanism. This indicated that scale did not affect the performance of the connection (besides the obvious strength and stiffness differences).
2. The inclusion of U-bars forced the failure into the CFST, increasing the capacity (~60%), increasing the stiffness, and positively affecting the energy dissipation capabilities.
3. A 33% increase in concrete strength resulted in a 33% increase in the initiation of damage and ultimate load capacity of the pile indicating that the effect of concrete strength on cap performance may be 1 to 1.
4. Predicted values from the moment-rotation methodology were compared to the measured values and the average measured-to-predicted ratio was 0.95. It was determined that the methodology tends to overpredict capacities for connection without U-bars and underpredict the capacities for those with U-bars.

The results of this research provide substantial insights into the behavior of CFST to concrete pile cap connections under various conditions and validates the use of the moment-rotation methodology as a reliable tool for capacity prediction.

### Acknowledgements

The authors would like to acknowledge the financial support for this project provided by the Montana Department of Transportation (MDT). The authors would also like to recognize and thank the MDT Research Section and the technical panel for their participation in this project, particularly Lenci Kappes. Furthermore, the authors would like to acknowledge Concrete Connections out of Bozeman, Montana for their efforts in bending the rebar used in this research. Their workmanship, timeliness, and generosity were vital to the success of the project. Additionally, this research would not have been possible without the support of several undergraduate and graduate student research assistants. In particular, the authors would like to thank James Starke, Emtiaz Ahmed, Jake Artis, Dawson Peterman, Axel Tanner, and Ethan Turner for their diligent help in the lab during both construction and testing phases of the project. The authors would also like to thank Professor Tim White for his help throughout the entire duration of the project on various technical components where experience and good judgement was necessary.

This document is printed at state expense. Information on the cost of producing this publication may be obtained by contacting the Montana Department of Administration.

Alternative accessible formats of this document will be provided on request. Persons who need an alternative format should contact the Human Resources and Occupational Safety Division, Department of Transportation, 2701 Prospect Avenue, PO Box 201001, Helena, MT 59620. Telephone 406-444-9229. Those using a TTY may call 1(800)335-7592 or through the Montana Relay Service at 711.